



\overline{XJ} -F100W

ADVANCED SERIES

LampFree. MercuryFree. StressFree.
The Casio Advanced Series is the next generation in LampFree. Advanced Series Projectors provide high brightness, up to 3500 ANSI lumens in XGA and WXGA resolutions.
Two (2) HDMI inputs provide connectivity with all current display technology without the need for switching cables. A high power USB port (DC 5V 2A) provides direct power for USB stick devices and eliminates the need for a separate power supply. All Casio LampFree Projectors are built to last and backed by an "Industry best" 3 year parts and labor warranty plus 5 years or 10,000 hours on the light source out of the box.

Key Features

- Two (2) HDMI inputs
- Power USB port (DC 5V 2A)
- · Dust resistant design
- Instant Light Control 7 level
- · High Power 16 watt speaker
- 1.5 X Manual Zoom/Focus Lens
- DLP® Technology

LampFree Features

- · Laser & LED Light Source
- · Long Life, 20,000 hour estimated operating life
- · No Lamp replacement required
- No Down Time
- Low Power Consumption
- Mercury Free
- Instant On (5 seconds to full brightness)
- · Instant Off no cool down required

Terminal Interface



CASIO Projector Specifications	ADVANCED SERIES XJ-F100W
	WXGA
Native Resolution	1280 x 800
	16:10
Native Aspect Ratio Brightness	3500 lumens
	0.65 -inch DLP® chip
Display Device Contrast Ratio	20,000:1
Lens Type	1.5X Manual Zoom & Focus 33%
Lens Offset	33.0
Light Source	Laser & LED
Estimated Light Source Life	Up to 20,000 Hours
Screen Size (Min-Max)	35 to 300-inch diagonal
Projection Range	-
60-inch screen	5.4 ~ 7.9 ft
100-inch screen	9.2 ~ 13.5 ft
Minimum Throw Distance	3.0 ft
Throw Ratio	1.32-1.93:1
Keystone Correction	Vertical +30° (Auto) Vertical + or - 30° (Manual)
Color Reproduction	Full color (up to 1.07 billion colors)
Power Source	AC100~240V, 50/60Hz
Power Consumption	
Operating	205 W - light control "off" Bright selected
	165 W - light control "on" and "Light Output 7" selected
Standby	0.12 W
TERMINAL CONNECTIVITY	
Video Signal Compatibility	
Video Systems	NTSC/ PAL/ PAL-N/ PAL-M/ PAL60/ SECAM
DTV/HDTV	480i/480p/576i/576p/720p/1080i/1080p
Maximum Computer Input	WUXGA (1920 x 1200) *Reduced blanking signal
INPUTS	
DCD/C	mini D-Sub 15 pin x 1 (Also use as YCbCr/YPbPr input— commercially
RGB/Component Video Input	available adapter required)
HDMI	HDMI Type A x 2, HDCP and audio support
Composite Video	Composite Video (RCA) x 1, S-Video
Audio	RCA (R/L) x 1, 3.5mm stereo mini jack x 1
USB Power Supply	Yes, DC 5V 2A
USB Input (Host)	No
USB Display	No
Logo Transfer	Micro B(USB1.1) x1
Built-in Memory	No
Wireless Capability	No
OUTPUTS	
Audio	3.5mm Stereo Mini Jack x 1 (variable audio)
AUDIO AND CONTROL SYSTEMS	(
Audio system	16W Monaural Speaker
Control Terminal	
RS-232	— RS-232C (D sub 9 pin) x 1, Cross Cable (Null Modem) required
RS-232 LAN	No
RS-232 LAN Control System Compatibility	
RS-232 LAN	No
RS-232 LAN Control System Compatibility	No No —
RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temp/Humidity	No
RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment	No No —
RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode	No No — 41-95°F / 20~80% (non condensation)
RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7)	No No — 41~95°F / 20~80% (non condensation) Yes (for operation 5,000-10,000 ft)
RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temp/Humidity	No No 41-95°F / 20-80% (non condensation) Yes (for operation 5,000-10,000 ft) Yes – Note: Projector must be turned off once every 24 hours
RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning	No No 41-95°F / 20~80% (non condensation) Yes (for operation 5,000-10,000 ft) Yes – Note: Projector must be turned off once every 24 hours Free Orientation Yes
RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range	No No No No 41-95°F / 20-80% (non condensation) Yes (for operation 5,000-10,000 ft) Yes – Note: Projector must be turned off once every 24 hours Free Orientation Yes 16.4 ft Maximum
RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility	No No No No No A1-95°F / 20-80% (non condensation) Yes (for operation 5,000-10,000 ft) Yes – Note: Projector must be turned off once every 24 hours Free Orientation Yes 16.4 ft Maximum Kensington™ Compatible / Power On Password
RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable	No No No No No No 41-95°F / 20-80% (non condensation) Yes (for operation 5,000-10,000 ft) Yes – Note: Projector must be turned off once every 24 hours Free Orientation Yes 16.4 ft Maximum Kensington™ Compatible / Power On Password Yes, available and sold separately by 3rd party vendors
RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mount Screws	No N
RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mount Screws	No N
RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mount Screws Limited Warranty	No N
RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mount Screws Limited Warranty Included Accessories	No N
RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mount Screws Limited Warranty Included Accessories Optional Accessories	No N
RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mount Screws Limited Warranty Included Accessories Optional Accessories Cabinet Color	No N
RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mount Screws Limited Warranty Included Accessories Optional Accessories Cabinet Color	No N
RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable	No N
RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mount Screws Limited Warranty Included Accessories Optional Accessories Cabinet Color Dimension (W x D x H)	No N
RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mount Screws Limited Warranty Included Accessories Optional Accessories Optional Accessories Cabinet Color Dimension (W x D x H) Including Projections	No N
RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mount Screws Limited Warranty Included Accessories Optional Accessories Cabinet Color Dimension (W x D x H) Including Projections Excluding Projections Weight	No N
RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mount Screws Limited Warranty Included Accessories Optional Accessories Optional Accessories Cabinet Color Dimension (W x D x H) Including Projections Excluding Projections Weight Packing Information	No N
RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment	No N
RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment Operating Temp/Humidity High Altitude Mode Extended operation (24 x 7) Rotation Projection Closed Captioning Remote Control Range Security Compatibility Ceiling Mountable Ceiling Mount Screws Limited Warranty Included Accessories Optional Accessories Optional Accessories Cabinet Color Dimension (W x D x H) Including Projections Excluding Projections Weight Packing Information Carton Dimensions Carton Dimensions Carton Weight	No N
RS-232 LAN Control System Compatibility OTHER INFORMATION Usage Environment	No N

© 2016 Casio America, Inc. All rights reserved. Casio is a registered trademark of Casio Computer Co., Ltd. In the United States and/or other countries. Specifications were thought to be correct at time of publication. All specifications and features are subject to change without notice. DLP, the DLP logo and the DLP medallion are trademarks of Texas Instruments. XGA is a registered trademarks of International Business Machines Corporation in the United States. HDMI is a trademark or registered trademark of HDMI Licensing, LtC. Other product names or company names on this specification brochure are either trademarks or registered trademarks of their respective owners.

Designed and Manufactured by Casio in Japan TAA Compliant